



※1 Including valuable materials

※2 Proportion of weight that cannot be recycled is 1%

■ Exhaust gas concentrations

| Smoke emitting equipment | Soot(g/m ³ N) | | | SOx(m ³ N/h) | | | NOx(ppm)- converted at 4% oxygen | | |
|--------------------------|--------------------------|--------------------|------------------------|-------------------------|--------------------|------------------------|----------------------------------|--------------------|------------------------|
| | Regulatory standard | Voluntary standard | Measurements (Average) | Regulatory standard | Voluntary standard | Measurements (Average) | Regulatory standard | Voluntary standard | Measurements (Average) |
| Facility 1 | 0.3 | | 0.004 | | | | 75 | | 49.5 |
| Facility 2 | 0.3 | | 0.004 | | | | 65 | | 42 |
| Facility 3 | 0.3 | | 0.004 | | | | 110 | | 64.5 |

■ Effluent Quality – Discharged into public sewer

Effluent facilities are not regulated under Japan's Water Pollution Control Act and Sewerage Act and effluent flows directly into the public sewage system, so no measurements are taken.

■ Use of harmful air pollutants

Dichloromethane, trichloroethylene, tetrachloroethylene, chloroform, vinyl chloride monomers, 1,3-butadiene, benzene, acrylonitrile, 1,2-dichloroethane, formaldehyde, trinickel disulfide, nickel sulfate, acetaldehyde – No records of the use of these substances